2SCK hose

Composition: ·Inner tube: special synthetic rubber resistant to hydraulic oil.
·Reinforcement: two braids of steel wire.
·Cover: synthetic rubber resistant to oil, abrasion and weather.

Working temperature: From -40º C to +100º C.

Part nº	DN	Ø in	Ø out	Working Pressure (bar)	Working pressure (psi)	Burst pressure (bar)	Burst pressure (psi)	Bending radius (mm)	Weight (kg/m)
MS2SCK10	5/8"	16.4	23,6	290	4.205	1.160	16.820	130	0.651
MSDQ2SCK04	1/4"	6,6	13,4	450	6.525	1.800	26.100	45	0,27
MSDQ2SCK05	5/16"	8,3	15	420	6.090	1.680	24.360	60	0,31
MSDQ2SCK06	3/8"	9,9	17	385	5.585	1.540	22.340	70	0,39
MSDQ2SCK08	1/2"	13,0	20,7	345	5.000	1.380	20.015	90	0,52
MSDQ2SCK10	5/8"	16,4	23,6	290	4.205	1.160	16.820	130	0,65
MSDQ2SCK12	3/4"	19,5	27,7	280	4.060	1.120	16.240	160	0,79
MSDQ2SCK16	1"	26	35,6	200	2.900	800	11.600	210	1,15

M2SCK codes are TRALE brand

The information gathered in this technical documentation (Catalogue) has an informative character and can be modified without previous notice. DICSA will not accept any type of responsibility resulting from an inappropriate use of the product, except the ones related to manufacturing defects.