



| Artikel        | DN    | Ø int | Ø ext | Betriebs-<br>Druck<br>(bar) | Betriebs-<br>Druck<br>(psi) | Platz- Druck<br>(bar) | Platz- Druck<br>(psi) | Biege-<br>Radius<br>(mm) | Gewicht<br>(kg/m) |
|----------------|-------|-------|-------|-----------------------------|-----------------------------|-----------------------|-----------------------|--------------------------|-------------------|
| <b>M461206</b> | 3/8"  | 9,5   | 20,4  | 276                         | 4.002                       | 1.104                 | 16.008                | 130                      | 0,63              |
| <b>M461208</b> | 1/2"  | 12,7  | 23,8  | 276                         | 4.002                       | 1.104                 | 16.008                | 180                      | 0,790             |
| <b>M461210</b> | 5/8"  | 15,9  | 27,4  | 276                         | 4.002                       | 1.104                 | 16.008                | 200                      | 1,120             |
| <b>M461212</b> | 3/4"  | 19    | 30,7  | 276                         | 4.002                       | 1.104                 | 16.008                | 240                      | 1,230             |
| <b>M461216</b> | 1"    | 25,4  | 38    | 276                         | 4.002                       | 1.104                 | 16.008                | 300                      | 1,880             |
| <b>M461220</b> | 1"1/4 | 31,8  | 47    | 207                         | 3.001,5                     | 828                   | 12.006                | 420                      | 2,690             |
| <b>M461224</b> | 1"1/2 | 38    | 53,5  | 172                         | 2.494                       | 688                   | 9.976                 | 500                      | 3,400             |