EN 856 4SH Hose

Composition: ·Inner tube: special synthetic rubber resistant to mineral, vegetable and hydraulic oil.
·Reinforcement: four braids of steel wire.
·Cover: synthetic rubber, resistant to oil, abrasion and weather.

Working temperature: From -40º C to +100º C.

Part nº	DN	Ø in	Ø out	Working Pressure (bar)	Working pressure (psi)	Burst pressure (bar)	Burst pressure (psi)	Bending radius (mm)	Weight (kg/m)
MS456932	2''	51,2	68,1	250	3.625	1.000	14.504	700	5,00
MDDS456912	3/4"	19,0	31,5	420	6.090	1.680	24.360	280	1,70
MDDS456916	1"	25,2	38,5	380	5.510	1.520	22.040	340	2,50
MDDS456920	1"1/4	32,2	45,2	350	5.075	1.400	20.300	460	3,00
MDDS456924	1"1/2	38,5	53,5	290	4.206	1.160	16.824	560	3,60
MDDS456932	2"	51,2	68,1	250	3.625	1.000	14.504	700	5,00

The information gathered in this technical documentation (Catalogue) has an informative character and can be modified without previous notice. DICSA will not accept any type of responsibility resulting from an inappropriate use of the product, except the ones related to manufacturing defects.