

**Material:** Steel**Seals:** NBR**Working temperature:** -25°C / +100°C**Working pressure:** 200-300 bar

Part n°	R1	Working Pressure (bar)	ISO size	BG size	Coupling	Water flow(l/min)	FLOW MAX (l/min)	L	L1	L2	HEX 1	HEX 2	ØE	A
<b>A701104</b>	1/4" NPT	300	6,3	1	M	12	20	76,3		38		19		14,2
<b>A701106</b>	3/8" NPT	250	10	2	M	23	35	85,5		42,5		24		19
<b>A701108</b>	1/2" NPT	200	12,5	3	M	30	55	96,5		48		27		20,5
<b>A701112</b>	3/4" NPT	200	19	4	M	60	120	114,5		57		34		27,9
<b>A701116</b>	1" NPT	200	25	5	M	80	160	131,5		65,5		41		31,3
<b>A701204</b>	1/4" NPT	300	6,3	1	H	12	20	76,3	55,5		19		27	14,2
<b>A701206</b>	3/8" NPT	250	10	2	H	23	35	85,5	63		24		34	19
<b>A701208</b>	1/2" NPT	200	12,5	3	H	30	55	96,5	70		27		38	20,5
<b>A701212</b>	3/4" NPT	200	19	4	H	60	120	114,5	86		34		47	27,9
<b>A701216</b>	1" NPT	200	25	5	H	80	160	131,5	99		41		52	31,3