




Rubinetto a sfera maschio DIN 2353 Serie L

Acciaio al carbonio

1/1



Standard o-ring: NBR
Sede della esfera: POM (poliosimetilene)

Codice	DN	ØD1	R1	PRESSIONE MAX. (bar)	HEX 1	A	B	C	D	E	H	I	K	L	V
GB2V 6 L	6	6L	M12x1.5	500	22	67	37	32	13	110	68	26	28	4,5	5
GB2V 8 L	6	8L	M14x1.5	500	22	67	37	32	13	110	68	26	28	4,5	5
GB2V 10 L	8	10L	M16x1.5	500	27	74	42	40	17	110	77	32	32	6,5	5
GB2V 12 L	10	12L	M18x1.5	500	27	74	42	40	17	110	77	32	32	6,5	5
GB2V 15 L	13	15L	M22x1.5	500	30	82	48	40	17	110	77	37,5	40	6,5	4,8
GB2V 18 L	13	18L	M26x1.5	400	30	82	48	40	17	110	77	37,5	40	6,5	4,8
GB2V 22 L	20	22L	M30x2	315	41	101	60	57	24	170	108	45	48	6,5	6,5
GB2V 28 L	25	28L	M36x2	315	50	108	65	64	28,5	170	115	55	57	6,7	6