



**Temperature range:** -50°C...+80°C (short time +120°C)

**Material:** HDPE

**High UV resistance**

**Protection against the abrasion**

| Part n°        | DN | Ø outer | Thickness (mm) | E   | L  | LENGTH (M) | M/PACK | PITCH |
|----------------|----|---------|----------------|-----|----|------------|--------|-------|
| AMUELLE HDPE13 | 13 | 16      | 1.3            | 1,3 | 13 | 25         | 25     | 13    |
| AMUELLE HDPE16 | 16 | 20      | 2              | 2   | 20 | 25         | 25     | 13    |
| AMUELLE HDPE20 | 20 | 25      | 2.2            | 2,2 | 24 | 25         | 25     | 20    |
| AMUELLE HDPE27 | 27 | 32      | 2.5            | 2,5 | 24 | 25         | 25     | 24    |
| AMUELLE HDPE35 | 35 | 40      | 2.7            | 2,7 | 24 | 25         | 25     | 24    |
| AMUELLE HDPE43 | 43 | 50      | 3.4            | 3,4 | 30 | 25         | 25     | 30    |
| AMUELLE HDPE56 | 56 | 63      | 3.7            | 3,7 | 37 | 25         | 25     | 37    |
| AMUELLE HDPE66 | 66 | 75      | 4.4            | 4,4 | 42 | 20         | 20     | 42    |