

Delivery water EPDM 125°C 10 BAR

1/1



Description and application: Industrial hose manufactured on a mandrel for water and hot water delivery designed for applications for industry and agriculture.
EPDM suitable for slurry, fertilisers and non-corrosive fluids

Composition: Inner tube: Black EPDM rubber.
Reinforcement: High tenacity textile.
Cover: SBR/EPDM black rubber, resistance to abrasion and atmospheric agents

Working temperature: -40 °C +125 °C

Safety factor: 3:1

Part nº	Ø in	Ø out	Working Pressure (bar)	Working pressure (psi)	Burst pressure (bar)	Burst pressure (psi)	Weight (kg/m)	Length (m)
WATER103061	30	40	10	150	30	450	0,85	61
WATER103261	32	42	10	150	30	450	0,87	61
WATER103520	35	45	10	150	30	450	0,99	20
WATER103540	35	45	10	150	30	450	0,99	40
WATER103820	38	48	10	150	30	450	1,05	20
WATER103840	38	48	10	150	30	450	1,05	40
WATER104020	40	50	10	150	30	450	1,00	20
WATER104040	40	50	10	150	30	450	1,00	40
WATER104520	45	55	10	150	30	450	1,20	20
WATER104540	45	55	10	150	30	450	1,20	40
WATER105120	51	61	10	150	30	450	1,40	20
WATER105140	51	61	10	150	30	450	1,40	40
WATER106020	60	72	10	150	30	450	1,60	20
WATER106040	60	72	10	150	30	450	1,60	40
WATER107620	76	87	10	150	30	450	2,00	20
WATER107640	76	87	10	150	30	450	2,00	40
WATER108020	80	92	10	150	30	450	2,15	20
WATER109020	90	102	10	150	30	450	2,30	20
WATER1010220	102	115	10	150	30	450	3,00	20