

Steam 7 bar EPDM 170°C

1/1



Description and application: Industrial hose manufactured on a mandrel design for the delivery of saturated steam up to 170°C.

Composition: Inner tube: Black EPDM rubber.
Reinforcement: High tenacity textile.
Cover: EPDM black rubber resistance to temperature, abrasion and atmospheric agents.
Micro-perforated

Working temperature: -40 °C +170 °C

Safety factor: 10:1

Part nº	Ø in	Ø out	Working Pressure (bar)	Working pressure (psi)	Burst pressure (bar)	Burst pressure (psi)	Bending radius (mm)	Weight (kg/m)	Length (m)
STEAM71320	13	24	7	100	70	1.000	80	0,37	20
STEAM71340	13	24	7	100	70	1.000	80	0,37	40
STEAM71620	16	28	7	100	70	1.000	100	0,46	20
STEAM71640	16	28	7	100	70	1.000	100	0,46	40
STEAM71920	19	31	7	100	70	1.000	140	0,55	20
STEAM71940	19	31	7	100	70	1.000	140	0,55	40
STEAM72520	25	37	7	100	70	1.000	170	0,62	20
STEAM72540	25	37	7	100	70	1.000	170	0,62	40
STEAM73220	32	46	7	100	70	1.000	240	0,95	20
STEAM73240	32	46	7	100	70	1.000	240	0,95	40
STEAM73820	38	53	7	100	70	1.000	300	1,20	20
STEAM73840	38	53	7	100	70	1.000	300	1,20	40
STEAM75120	51	68	7	100	70	1.000	380	1,75	20
STEAM75140	51	68	7	100	70	1.000	380	1,75	40