


Delivery air 20 BAR



Description and application: Industrial hose manufactured on a mandrel design for the delivery of compressed air and water in public works, mining and industrial services. Rubber specially formulated to resist low concentration oil mist and non- corrosive fluids

Composition: Inner tube: Special black rubber.
Reinforcement: High tenacity textile
Cover: SBR/EPDM black rubber, resistance to abrasion and atmospheric agents

Working temperature: -30 °C +80 °C

Safety factor: 3:1

Standard; EN ISO 2398:2017 Type 2 Class A

Part n°	Ø in	Ø out	Working Pressure (bar)	Working pressure (psi)	Burst pressure (bar)	Burst pressure (psi)	Weight (kg/m)	Length (m)
AIRWATER201320	13	23	20	300	60	900	0,35	20
AIRWATER201340	13	23	20	300	60	900	0,35	40
AIRWATER201520	15	25	20	300	60	900	0,40	20
AIRWATER201540	15	25	20	300	60	900	0,40	40
AIRWATER201620	16	26	20	300	60	900	0,43	20
AIRWATER201640	16	26	20	300	60	900	0,43	40
AIRWATER201920	19	30	20	300	60	900	0,55	20
AIRWATER201940	19	30	20	300	60	900	0,55	40
AIRWATER202520	25	36	20	300	60	900	0,70	20
AIRWATER202540	25	36	20	300	60	900	0,70	40
AIRWATER203020	30	42	20	300	60	900	0,90	20
AIRWATER203040	30	42	20	300	60	900	0,90	40
AIRWATER203220	32	44	20	300	60	900	0,95	20
AIRWATER203240	32	44	20	300	60	900	0,95	40
AIRWATER203520	35	47	20	300	60	900	1,03	20
AIRWATER203540	35	47	20	300	60	900	1,03	40
AIRWATER203820	38	50	20	300	60	900	1,10	20
AIRWATER203840	38	50	20	300	60	900	1,10	40
AIRWATER204020	40	52	20	300	60	900	1,15	20
AIRWATER204040	40	52	20	300	60	900	1,15	40
AIRWATER204520	45	58	20	300	60	900	1,40	20
AIRWATER204540	45	58	20	300	60	900	1,40	40
AIRWATER205120	51	65	20	300	60	900	1,75	20
AIRWATER205140	51	65	20	300	60	900	1,75	40
AIRWATER206020	60	76	20	300	60	900	2,20	20
AIRWATER206040	60	76	20	300	60	900	2,20	40
AIRWATER206320	63	79	20	300	60	900	2,30	20

Delivery air 20 BAR**2/2**

Part n°	Ø in	Ø out	Working Pressure (bar)	Working pressure (psi)	Burst pressure (bar)	Burst pressure (psi)	Weight (kg/m)	Length (m)
AIRWATER206340	63	79	20	300	60	900	2,30	40
AIRWATER207620	76	92	20	300	60	900	2,70	20
AIRWATER207640	76	92	20	300	60	900	2,70	40
AIRWATER2010211320	102	113	20	300	60	900	2,49	20
AIRWATER2010211340	102	113	20	300	60	600	2,49	40
AIRWATER2010220	102	118	20	300	60	900	3,20	20
AIRWATER2010240	102	118	20	300	60	900	3,20	40

AIRWATER2010211340, AIRWATER2010211320 flat type