

**Delivery air 20 BAR continuous series****1/1**

**Description and application:** manufactured for the delivery of water and compressed air. Design for general service applications in industry, construction and agriculture. Resistant to low concentration oil mist, suitable for pneumatic tools and industrial air compressors

**Composition:** Inner tube: Synthetic natural rubber, resistant to oil mist. Reinforcement: High tenacity textile Cover: Smooth natural and synthetic rubber, resistant to abrasion, ozone and atmospheric agents

**Working temperature:** -25°C + 70°C

**Safety factor:** 3:1

Part nº	Ø in	Ø out	Working Pressure (bar)	Working pressure (psi)	Burst pressure (bar)	Burst pressure (psi)	Weight (kg/m)	LONGITUD (M)
<b>AIR2006100</b>	6	12	20	300	60	900	0.160	100
<b>AIR2008100</b>	8	15	20	300	60	900	0.195	100
<b>AIR2010100</b>	10	17	20	300	60	900	0.270	100
<b>AIR201350</b>	13	22	20	300	60	900	0.395	50
<b>AIR201650</b>	16	26	20	300	60	900	0.450	50
<b>AIR201920</b>	16	26	20	300	60	900	0.450	50
<b>AIR201950</b>	19	29	20	300	60	900	0.585	50
<b>AIR202550</b>	25	37	20	300	60	900	0.890	50