



Description and application: Industrial hose manufactured on a mandrel to convey dry or wet abrasive materials. Particularly suitable for sand and shot blasting, gunite and mortars. High performance and durability

Composition: Inner: Highly abrasion resistant, conductive, black NR rubber.
Reinforcement: High tenacity textile.
Cover: black, antistatic, abrasion and weather resistant special rubber

Temperature: -40 °C +70 °C

Safety Factor: 3:1

Abrasion resistance: 35mm3 ISO 4649-2021

Part nº	Ø in	Ø out	Working Pressure (bar)	Working pressure (psi)	Burst pressure (bar)	Burst pressure (psi)	Weight (kg/m)	Length (m)
SHOTBLAST121361	13	25	12	180	36	540	0.46	61
SHOTBLAST121920	19	33	12	180	36	540	0.66	20
SHOTBLAST121940	19	33	12	180	36	540	0.66	40
SHOTBLAST122520	25	39	12	180	36	540	0.83	20
SHOTBLAST122540	25	39	12	180	36	540	0.83	40
SHOTBLAST122561	25	39	12	180	36	540	0.83	40
SHOTBLAST123220	32	48	12	180	36	540	1.14	20
SHOTBLAST123240	32	48	12	180	36	540	1.14	40
SHOTBLAST123820	38	54	12	180	36	540	1.30	20
SHOTBLAST123840	38	54	12	180	36	540	1.30	40
SHOTBLAST124020	40	57	12	180	36	540	1.50	20
SHOTBLAST124040	40	57	12	180	36	540	1.50	40
SHOTBLAST125120	51	69	12	180	36	540	1.98	20
SHOTBLAST125140	51	69	12	180	36	540	1.98	40
SHOTBLAST126020	60	80	12	180	36	540	2.40	20
SHOTBLAST127620	76	96	12	180	36	540	2.70	20
SHOTBLAST128020	80	100	12	180	36	540	3.25	20
SHOTBLAST129020	90	110	12	180	36	540	3.50	20
SHOTBLAST1210220	102	122	12	180	36	540	4.00	20