



**Description and application:** Industrial hose manufactured on a mandrel for the delivery of abrasive materials in wet conditions. Suitable shotcrete (gunite), and mortar. Engineered for excellent performance and extended service life.

**Composition:** Inner tube: Black conductive NR rubber highly resistant to abrasion

Reinforcement: High tenacity textile

Cover: Special black rubber, anti-static, resistant to abrasion and atmospheric agents.

**Working temperature:** -40 °C +85 °C

**Safety factor:** 2.5:1

Part nº	Ø in	Ø out	Working Pressure (bar)	Working pressure (psi)	Burst pressure (bar)	Burst pressure (psi)	Bending radius (mm)	Weight (kg/m)	Length (m)
<b>PLASTER402520</b>	25	37	40	600	100	1.500	150	0.65	20
<b>PLASTER402540</b>	25	37	40	600	100	1.500	150	0.65	40
<b>PLASTER403520</b>	35	49	40	600	100	1.500	200	1.10	20
<b>PLASTER403540</b>	35	49	40	600	100	1.500	200	1.10	40
<b>PLASTER405120</b>	51	68	40	600	100	1.500	295	1.85	20
<b>PLASTER405140</b>	51	68	40	600	100	1.500	295	1.85	40
<b>PLASTER406520</b>	65	85	40	600	100	1.500	390	2.85	20