



**Description and application:** Industrial hose manufactured on a mandrel, suitable for the delivery of saturated steam up to 165°C in the food industry

**Composition:** Inner tube: White FDA approved EPDM rubber  
Reinforcement: High tenacity textile  
Cover: Blue EPDM rubber, resistant to heat, abrasion and atmospheric agents.

**Working temperature:** Steam -40 °C +165 °C / hot water -40°C +120°

**Safety factor:** Steam 10:1 / hot water 20 Bar 3:1

Part nº	Ø in	Ø out	Working Pressure (bar)	Working pressure (psi)	Burst pressure (bar)	Burst pressure (psi)	Weight (kg/m)	Length (m)
<b>STEAMFDA61320</b>	13	24	6	87	60	870	0.40	20
<b>STEAMFDA61340</b>	13	24	6	87	60	870	0.40	40
<b>STEAMFDA61620</b>	16	28	6	87	60	870	0.50	20
<b>STEAMFDA61640</b>	16	28	6	87	60	870	0.50	40
<b>STEAMFDA61920</b>	19	31	6	87	60	870	0.57	20
<b>STEAMFDA61940</b>	19	31	6	87	60	870	0.57	40
<b>STEAMFDA62520</b>	25	37	6	87	60	870	0.70	20
<b>STEAMFDA62540</b>	25	37	6	87	60	870	0.70	40