



Referencia giro: BTD...I=Referencia giro izquierda
BTD...D=Referencia giro derecha

Min 400 rpm

Flange and cover: Cast iron

Artículo	R1	R2	Pres. max. (bar)	Pres. punta (bar)	R.P.M. (max)	cm ³ / rev	A	B
BTD3220I01	3/4" BSP	3/4" BSP	200	250	3000	22 CC	130,5	63,5
BTD3260I01	3/4" BSP	3/4" BSP	200	250	3000	26 CC	133,5	65
BTD3280I01	1" BSP	3/4" BSP	200	250	3000	28 CC	134,5	65,5
BTD3320I01	1" BSP	3/4" BSP	200	250	3000	32 CC	137,5	67
BTD3360I01	1" BSP	3/4" BSP	200	250	3000	36 CC	140,5	68,5
BTD3420I01	1" BSP	3/4" BSP	200	250	2800	42 CC	144,5	70,5
BTD3460I01	1" BSP	3/4" BSP	200	250	2400	46 CC	147,5	72

Bombas de engranajes

Bombas engranajes Grupo III Izquierda

Tapa eur/eje conico 1:8 brida roscada Gr.III

Página: 2/2

Artículo	R1	R2	Pres. max. (bar)	Pres. punta (bar)	R.P.M. (max)	cm ³ / rev	A	B
BTD3500I01	1" BSP	3/4" BSP	200	250	2400	50 CC	150	73,5
BTD3550I01	1" BSP	3/4" BSP	200	250	2400	55 CC	153,5	75

R1 = aspiración; R2 = presión