



Distribuidor 3/8" BSP, 50L, acc. palanca y retorno por muelle a posición central. Limit.



TYPE	E		F		Weight	
	mm	in	mm	in	kg	lb
YFM50/1	88	3.46	60	2.36	2.50	5.5
YFM50/2	133	5.24	97	3.82	4.10	9.0
YFM50/3	168	6.61	132	5.20	5.5	12.1
YFM50/4	203	7.99	167	6.6	6.90	15.2
YFM50/5	238	9.4	202	8.0	8.30	18.3
YFM50/6	273	10.7	237	9.3	9.70	21.4
YFM50/7	308	12.1	272	10.7	11.10	24.5
YFM50/8	343	13.5	307	12.1	12.50	27.6



Roscas P/T 1/2" - A/B 3/8"

Artículo	Detalles	ROSCA TOMAS	Caudal máx. (l/min)	Pres. max. (bar)	Nº palancas
YFM50/1 3/8 1P DE	D/E	3/8" BSP	50	250	1
YFM50/1 3/8 1P SE	S/E	3/8" BSP	50	250	1
YFM50/2 3/8 2P DD	D/E	3/8" BSP	50	250	2
YFM50/3 3/8 3P DDD	D/E	3/8" BSP	50	250	3
YFM50/4 3/8 4P DDDD	D/E	3/8" BSP	50	250	4
YFM50/5 3/8 5P DDDDD	D/E	3/8" BSP	50	250	5
YFM50/6 3/8 6P DDDDDD	D/E	3/8" BSP	50	250	6

*Para 7 y 8 palancas consultar.