

Antirretorno simple pilotaje en bloque (en T)

ref VSD...



ref ASPP



Material Cuerpo de Acero / NBR

Presión de Apertura VSD 2 bar / ASPP 1/4 4 bar ASPP 3/8 Y 1/2 3 bar

Artículo	R1	Caudal máx. (l/min)	Pres. max. (bar)	Ratio pilotaje	ØG	A	B	D	E	F	H	I	L
VSD 1/4-1R	1/4" BSP	12	350	1:4	6.5	126	63.6	29	51.6	9	30	45	15
VSD 3/8-20L-1R	3/8" BSP	20	300	1:4	*	126	63.6	29	*	*	30	45	15
VSD 3/8-1R	3/8" BSP	30	300	1:6	8	158	90	40	75	17	40	60	20
VSD 1/2-1R	1/2" BSP	45	300	1:4	8	174	90	40	75	17	40	60	20
VSD 3/4-1R	3/4" BSP	85	280	1:3.6	9	212	120	60	104	16	50	70	25
ASPP 1/4 D	1/4" BSP	12	350	1:4									
ASPP 1/4 I	1/4" BSP	12	350	1:4									
ASPP 3/8 D	3/8" BSP	30	300	1:6									
ASPP 3/8 I	3/8" BSP	30	300	1:6									
ASPP 1/2 D	1/2" BSP	45	300	1:4									
ASPP 1/2 I	1/2" BSP	45	300	1:4									

*** Revisar PDF adjunto ***

* La válvula VSD 3/8-20L-1R no dispone de agujeros de fijación.