BSP Female threaded counter-flange

Stainless Steel AISI 316-L





Part nº	Serie	R1	Size	B	C	E	G	H	M
ZBCRG30808	3000 PSI	1/2" BSP	1/2"	13	38,1	17,48	36	16	M8
ZBCRG31212	3000 PSI	3/4" BSP	3/4"	19	47,63	22,23	36	18	M10
ZBCRG31616	3000 PSI	1" BSP	1"	25	52,37	26,19	38	18	M10
ZBCRG32020	3000 PSI	1"1/4 BSP	1"1/4	32	58,72	30,18	40	21	M10
ZBCRG32424	3000 PSI	1"1/2 BSP	1"1/2	38	69,85	35,71	45	25	M12
ZBCRG33232	3000 PSI	2" BSP	2"	51	77,77	42,88	45	25	M12
ZBCRG34040	3000 PSI	2"1/2 BSP	2"1/2	63	88,9	50,8	50	25	M12
ZBCRG34848	3000 PSI	3" BSP	3"	73	106,38	61,93	50	27	M16
ZBCRG35656	3000 PSI	3"1/2 BSP	3"1/2	89	120,65	69,85	48	27	M16
ZBCRG36464	3000 PSI	4" BSP	4"	99	130,18	77,77	48	27	M16
ZBCRG60808	6000 PSI	1/2" BSP	1/2"	13	40,49	18,24	36	16	M8
ZBCRG61212	6000 PSI	3/4" BSP	3/4"	19	50,8	23,8	35	21	M10
ZBCRG61616	6000 PSI	1" BSP	1"	25	57,15	27,76	42	25	M12
ZBCRG62020	6000 PSI	1"1/4 BSP	1"1/4	32	66,68	31,75	45	27	M14
ZBCRG62424	6000 PSI	1"1/2 BSP	1"1/2	38	79,38	36,5	50	30	M16
ZBCRG63232	6000 PSI	2" BSP	2"	51	96,82	44,45	65	37	M20

The information gathered in this technical documentation (Catalogue) has an informative character and can be modified without previous notice. DICSA will not accept any type of responsibility resulting from an inappropriate use of the product, except the ones related to manufacturing defects.